



Transition fittings PE/steel

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- Electrofusion weldable
- PE coated for corrosion resistance
- * Steel pipe galvanized

	d	d1	Code	Weight	L	L1	L2
	(mm)	(inch)		(kg)	(mm)	(mm)	(mm)
*	20	½	775 641 502	0.450	425	15	80
	25	¾	775 641 507	0.658	463	35	90
	32	1	775 641 510	0.988	460	35	96
	40	1 ¼	775 641 514	1.208	470	35	100
	50	1 ½	775 641 518	1.355	480	35	110
	63	2	775 641 524	2.011	480	35	110
	75	2 ½	775 641 632	2.983	540	35	127
	90	3	775 641 636	3.762	580	45	141
	110	3	775 641 640	4.381	580	45	145
	110	4	775 641 641	6.633	585	45	145
	125	4	775 641 645	6.833	585	45	148
	160	6	775 641 655	12.406	610	45	158
	180	6	775 641 659	11.935	610	45	168
	200	8	775 642 664	19.647	630	45	155
	225	8	775 642 669	20.154	607	45	145
	250	8	775 642 665	21.354	630	45	200
	250	10	775 642 666	30.000	640	45	140
	280	10	775 642 673	31.000	640	45	160
	315	12	775 642 672	35.000	725	45	220
	355	12	775 642 675	49.000	735	45	260
	400	16	775 642 678	94.000	770	45	190

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>