



## Product Inflex

**Producer** Pipelife Sverige AB, Ljung, Sweden (DIM 16 and 20mm)  
Pipelife Deutschland GmbH Germany (25, 32, 40 and 50mm)

**Usage** Indoor electro installation

**Information** INFLEX, flexible corrugated installation pipe in PP.

<b>Technical data</b>	Dimensions:	OD 16mm	ID 11,4mm	
		OD 20mm	ID 13,9mm	
		OD 25mm	ID 18,5mm	
		OD 32mm	ID 25,1mm	
		OD 40mm	ID 32,0mm	
		OD 50mm	ID 40,2mm	
		Halogen free:	Yes	
		Flame retardant:	Yes	
		Bending strength:	Flexible	
		With sleeve:	No	
		Compression strength:	Medium (3)	
		Impact strength:	Medium (3)	
		Flush mounted:	Yes	
		Surface mounted :	Yes	
	Suitable for installation in wood:	Yes		
	Suitable for hollow installation:	Yes		
	Suitable for concrete installation:	Yes		
	Machine and system installation:	No		
	Suitable for subsurface installation:	Yes		
	Outdoor installation:	No		
	Underground installation:	No		
	Operating temperature:	-25degC to 90degC		
	Color of pipe:	Grey		

**Marking** "Pipelife PP [DIM] 33 422 267—10 [SEO] alt. [DEB]"

**Quality** Pipelife quality system according to EN ISO 9001:2000

**Approvals** Pipelife Inflex produced according to EN 61386-1 and -22  
Certificate Intertek reference No: 1908359  
VDE Zeichengenehmigung Certificate No: 40004853